



# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Revision Date: 06/04/2015 Date of issue: 06/04/2015

Version: 1.1

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Name:** Presoftened Paste Rubbing Compound for Medium Oxidation

**Product Code:** 082614

**Synonyms:** Boat Wax

#### Intended Use of the Product

Boat Wax

#### Name, Address, and Telephone of the Responsible Party

##### Company

Star brite Inc.  
4041 SW 47<sup>th</sup> Avenue  
Fort Lauderdale, FL 33314  
(954)587-6280

[www.starbrite.com](http://www.starbrite.com)

#### Emergency Telephone Number

**Emergency Number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Full text of H-phrases: see section 16

#### Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Warning

##### Hazard Statements (GHS-US)

: H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.

##### Precautionary Statements (GHS-US)

: P261 - Avoid breathing vapors, spray, mist.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear eye protection, protective gloves, protective clothing.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

#### Other Hazards

Prolonged or repeated exposure may cause dermatitis and defatting. May aggravate those with pre-existing skin conditions.  
Aquatic Acute 3

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Aquatic Chronic 3

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

**Unknown Acute Toxicity (GHS-US)** Not available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	0.1 - 1; 1 - 5; 5 - 10; 10 - 30	Flam. Liq. 4, H227 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, heavy aliphatic	(CAS No) 64742-96-7	0.1 - 1; 1 - 5; 5 - 10; 10 - 30	Flam. Liq. 4, H227 Asp. Tox. 1, H304
Silica, amorphous, diatomaceous earth	(CAS No) 68855-54-9	3.04	STOT RE 1, H372
Pine oil	(CAS No) 8002-09-3	1.71	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 3, H402
Morpholine	(CAS No) 110-91-8	0.1 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapor), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318

More than one of the ranges of concentration prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause an allergic skin reaction. Causes skin irritation. Causes serious eye irritation.

**Inhalation:** May cause irritation to the respiratory tract.

**Skin Contact:** May cause an allergic skin reaction. Causes skin irritation.

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 5: FIRE FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Product will burn if heated to temperatures above its melting point.

**Explosion Hazard:** Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

**Reactivity:** Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

#### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not allow run-off from fire fighting to enter drains or water courses. Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

#### Reference to Other Sections

Refer to section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Avoid breathing vapor, mist, spray.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Eliminate ignition sources. Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

#### Environmental Precautions

Prevent entry to sewers and public waters.

#### Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

#### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

### SECTION 7: HANDLING AND STORAGE

#### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

#### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store away from oxidizers, combustible materials, and all ignition sources.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

#### Specific End Use(s)

Boat Wax.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

#### **Silica, amorphous, diatomaceous earth (68855-54-9)**

Yukon

OEL TWA (mg/m<sup>3</sup>)

300 particle/mL (as measured by Konimeter instrumentation)

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>		
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)
<b>Morpholine (110-91-8)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
<b>Mexico</b>	OEL TWA (ppm)	20 ppm
<b>Mexico</b>	OEL STEL (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
<b>Mexico</b>	OEL STEL (ppm)	30 ppm
<b>USA ACGIH</b>	ACGIH TWA (ppm)	20 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	20 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	20 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	30 ppm
<b>USA IDLH</b>	US IDLH (ppm)	1400 ppm (10% LEL)
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	71 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	20 ppm
<b>British Columbia</b>	OEL TWA (ppm)	20 ppm
<b>Manitoba</b>	OEL TWA (ppm)	20 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	71 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	20 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	20 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	20 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	30 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	20 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	30 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	20 ppm
<b>Ontario</b>	OEL TWA (ppm)	20 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	20 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	71 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	20 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	30 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	20 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	30 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	20 ppm

### Exposure Controls

**Appropriate Engineering Controls:** Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

**Personal Protective Equipment:** Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** A respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2-1992 or MSHA 30 CFR 72.710 (where applicable) requirements must be followed whenever workplace conditions warrant respirator use.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Semi-solid off white paste
Odor	: Petroleum distillates
Odor Threshold	: Not available
pH	: 8.5
Evaporation Rate	: Not available
Melting/Freezing Point	: 50 °C (122 °F)
Boiling Point	: 93.3 °C (200 °F)
Flash Point	: > 62.9 °C (> 145 °F) Tag Closed Cup
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Specific Gravity	: 0.9599
Solubility	: Slightly soluble in water
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: 55000 cP at 22.8 °C (73 °F)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Heat, hot surfaces, sparks, open flames, and other ignition sources.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation. (pH: 8.5)

**Serious Eye Damage/Irritation:** Not classified (pH: 8.5)

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified.

**Reproductive Toxicity:** Not classified

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause irritation to the respiratory tract.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Causes skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

### Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

<b>Silica, amorphous, diatomaceous earth (68855-54-9)</b>	
LD50 Oral Rat	> 2000 mg/kg
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h
<b>Solvent naphtha, petroleum, heavy aliphatic (64742-96-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.28 mg/l/4h
<b>Pine oil (8002-09-3)</b>	
LD50 Oral Rat	3200 mg/kg
LD50 Dermal Rat	5 g/kg
<b>Morpholine (110-91-8)</b>	
LD50 Oral Rat	1050 mg/kg
LD50 Dermal Rabbit	1900 mg/kg
LC50 Inhalation Rat	8000 ppm (Exposure time: 8 h)
ATE US (vapors)	11.00 mg/l/4h
<b>Silica, amorphous, diatomaceous earth (68855-54-9)</b>	
IARC Group	3
<b>Morpholine (110-91-8)</b>	
IARC Group	3

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>Pine oil (8002-09-3)</b>	
EC50 Daphnia 1	17 - 28 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
<b>Morpholine (110-91-8)</b>	
LC50 Fish 1	350 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC 50 Fish 2	375 - 460 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

**Persistence and Degradability** Not available

### Bioaccumulative Potential

<b>Silica, amorphous, diatomaceous earth (68855-54-9)</b>	
BCF Fish 1	(no known bioaccumulation)
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
BCF Fish 1	61 - 159
<b>Morpholine (110-91-8)</b>	
BCF Fish 1	0.3 - 2.8

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Log Pow</b>	-2.55 (at 25 °C)
----------------	------------------

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

**UN Number** Not regulated for transport

**UN Proper Shipping Name** Not regulated for transport

**Transport Hazard Class(es)**

**Additional Information** Not available

**Transport by sea** Not regulated for transport

**Air transport** Not regulated for transport

**Marine Pollutant** No

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

<b>Presoftened Paste Rubbing Compound for Medium Oxidation</b>	
--	--

<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard
--	---------------------------------

<b>Silica, amorphous, diatomaceous earth (68855-54-9)</b>
---

Listed on the United States TSCA (Toxic Substances Control Act) inventory
---

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>
---

Listed on the United States TSCA (Toxic Substances Control Act) inventory
---

<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard
--	-------------

	Immediate (acute) health hazard
--	---------------------------------

<b>Solvent naphtha, petroleum, heavy aliphatic (64742-96-7)</b>
---

Listed on the United States TSCA (Toxic Substances Control Act) inventory
---

<b>Pine oil (8002-09-3)</b>
-----------------------------

Listed on the United States TSCA (Toxic Substances Control Act) inventory
---

<b>Morpholine (110-91-8)</b>
------------------------------

Listed on the United States TSCA (Toxic Substances Control Act) inventory
---

### US State Regulations

<b>Presoftened Paste Rubbing Compound for Medium Oxidation</b>	
--	--

<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
--	--

<b>Silica, amorphous, diatomaceous earth (68855-54-9)</b>
---

RTK - U.S. - Pennsylvania - RTK (Right to Know) List
--

U.S. - Texas - Effects Screening Levels - Long Term
---

U.S. - Vermont - Permissible Exposure Limits - TWAs
---

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>
---

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
---

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
--

U.S. - Texas - Effects Screening Levels - Long Term
---

U.S. - Texas - Effects Screening Levels - Short Term
--

<b>Solvent naphtha, petroleum, heavy aliphatic (64742-96-7)</b>
---

U.S. - Texas - Effects Screening Levels - Long Term
---

U.S. - Texas - Effects Screening Levels - Short Term
--

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### **Pine oil (8002-09-3)**

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

### **Morpholine (110-91-8)**

U.S. - California - Precursor Chemicals  
U.S. - Colorado - Schedule II Controlled Substances  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Louisiana - Precursor Chemicals  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Michigan - Occupational Exposure Limits - Skin Designations  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations  
U.S. - Minnesota - Permissible Exposure Limits - STELs  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - Skin Designations  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - Skin Designations  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
U.S. - Oregon - Precursor Chemicals  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - Skin Designations  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - Skin Designations  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Canadian Regulations

<b>Presoftened Paste Rubbing Compound for Medium Oxidation</b>	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	
<b>Silica, amorphous, diatomaceous earth (68855-54-9)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Solvent naphtha, petroleum, heavy aliphatic (64742-96-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid
<b>Pine oil (8002-09-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Morpholine (110-91-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 06/04/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3


# Presoftened Paste Rubbing Compound for Medium Oxidation

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

- NFPA Health Hazard** : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA Fire Hazard** : 1 - Must be preheated before ignition can occur.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS