

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Name:** ProStar Diesel Stabilizer

**Product Code:** 844XX

#### Intended Use of the Product

Cleaner

#### Name, Address, and Telephone of the Responsible Party

Star brite Inc.  
 4041 SW 47<sup>th</sup> Avenue  
 Fort Lauderdale, FL 33314  
 (954)587-6280

[www.starbrite.com](http://www.starbrite.com)

#### Emergency Telephone Number

**Emergency number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226  
 Skin Irrit. 2 H315  
 Eye Dam. 1 H318  
 Skin Sens. 1 H317  
 STOT SE 3 H336  
 Asp. Tox. 1 H304

#### Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor  
 H304 - May be fatal if swallowed and enters airways  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H318 - Causes serious eye damage  
 H336 - May cause drowsiness or dizziness

##### Precautionary Statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.  
 P233+P242 - Keep container tightly closed. Use only non-sparking tools.  
 P240- Ground/bond container and receiving equipment.  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment.  
 P243 - Take precautionary measures against static discharge.  
 P261 - Avoid breathing vapors, spray, mist.  
 P264 - Wash hands, forearms, and exposed areas thoroughly after handling.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P272 - Contaminated work clothing should not be allowed out of the workplace.  
 P280 - Wear eye protection, protective gloves, protective clothing.  
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P303+P361+P353+P352 - IF ON SKIN (or hair): Remove/Take off immediately all

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a POISON CENTER or doctor/physician.  
P321 - Specific treatment (see Section 4).  
P331 - If swallowed, do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish.  
P391 - Collect spillage.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

**Other Hazards Not Contributing to the Classification:** Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Aquatic Chronic 2

H411 - Toxic to aquatic life with long lasting effects

P273 - Avoid release to the environment



GHS09

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Proprietary Polymer*	(CAS No) Proprietary (HMIRA Registry No) 8129	2 - 4	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	1 - 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 STOT SE 2, H371 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
N,N'-Disalicylidene-1,2-propanediamine	(CAS No) 94-91-7	0.2 - 0.6	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

\*The specific chemical identity has been withheld as a trade secret

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** May be fatal if swallowed and enters airways. Causes serious eye damage. Causes skin irritation. May cause drowsiness and dizziness.

**Inhalation:** May cause drowsiness or dizziness.

**Skin Contact:** Causes skin irritation. May cause an allergic skin reaction.

**Eye Contact:** Causes serious eye damage.

**Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** Exposure may produce an allergic reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If medical advice is needed, have product container or label at hand.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Reacts with (strong) oxidizers: (increased) risk of fire.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not allow run-off from fire fighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not get in eyes, on skin, or on clothing. Do NOT breathe (vapor, mist, gas).

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Eliminate ignition sources. Ventilate area. Stop leak if safe to do so.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Dangerous due to potential toxicity for the environment.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Specific End Use(s)** Cleaner

### Control Parameters

**Petroleum distillates, hydrotreated light (64742-47-8)**

British Columbia

OEL TWA (mg/m<sup>3</sup>)

200 mg/m<sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)

### Exposure Controls

**Appropriate Engineering Controls:** Ensure all national/local regulations are observed. Use explosion-proof equipment. Take precautionary measures against static discharges. Gas detectors should be used when flammable gases/vapours may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

**Personal Protective Equipment:** Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Wear fire/flammable resistant/retardant clothing.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Other Information:** When using, do not eat, drink or smoke.

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Amber
Odor	: Petroleum distillate
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: 0 °C (32 °F)
Freezing Point	: Not available
Boiling Point	: 180 °C (356 °F)
Flash Point	: 45 °C (113 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 0.78 (water = 1)
Specific Gravity	: Not available
Solubility	: Insoluble in water.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts with (strong) oxidizers: (increased) risk of fire.

**Chemical Stability:** Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**ID50 and IC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** Exposure may produce an allergic reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.

#### Information on Toxicological Effects - Ingredient(s)

**ID50 and IC50 Data:**

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (mg/l)	> 5.2 mg/l/4h

### SECTION 12: ECOLOGICAL INFORMATION

#### **Toxicity**

**Ecology - General:** Toxic to aquatic life with long lasting effects.

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

#### **Persistence and Degradability**

<b>ProStar Diesel Stabilizer</b>	
Persistence and Degradability	Not established.

#### **Bioaccumulative Potential**

<b>ProStar Diesel Stabilizer</b>	
Bioaccumulative Potential	Not established.

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
BCF fish 1	61 - 159

**Mobility in Soil:** Not available

#### **Other Adverse Effects**

**Other Information:** Avoid release to the environment.

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Hazardous waste due to toxicity.

### SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

#### UN Number

UN-No.(DOT) : 1268  
DOT NA no. : UN1268  
UN-No. (TDG) : UN1268  
UN-No. (IMDG) : 1268  
UN-No.(IATA) : 1268

#### UN Proper Shipping Name

**Proper Shipping Name (DOT)** : PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III, Marine Pollutant

**Proper Shipping Name (TDG)** : PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III, Marine Pollutant

**Proper Shipping Name (IATA)** : PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III

**Proper Shipping Name (IMDG)** : PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III, Marine Pollutant

**Transport Document Description (DOT)** : UN1268 PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III, Marine Pollutant

**Transport Document Description (TDG)** : UN1268 PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III, Marine Pollutant

**Transport Document Description (adr) (IMDG/IATA)** : UN1268 PETROLEUM PRODUCTS, N.O.S. (Petroleum distillates, hydrotreated light), 3, III, Marine Pollutant

#### Transport Hazard Class(es)

**Department Of Transportation (DOT) Hazard Classes** : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

**Hazard Labels (DOT)** : 3 - Flammable liquid



**Packing Group (DOT)** : III - Minor Danger

**DOT Special Provisions (49 CFR 172.102)** : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2).  
Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 Cfr 173.xxx)	: 150
DOT Packaging Non Bulk (49 Cfr 173.xxx)	: 203
DOT Packaging Bulk (49 Cfr 173.xxx)	: 242
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Hazard Labels (TDG)	: 3 - Flammable liquids



Packing Group (TDG)	: III - Minor Danger
Explosive Limit And Limited Quantity Index	: 5
Marine Pollutant	: P
Passenger Carrying Road Vehicle Or Passenger Carrying Railway Vehicle Index	: 60
Class (IMDG)	: 3
Danger Labels (IMDG)	: 3



Packing Group (IMDG)	: III
Class (IATA)	: 3

Hazard Labels (IATA)	: 3
----------------------	-----



Packing Group (IATA)	: III - Minor Danger
Marine Pollutant	: P



### Additional Information

Emergency Response Guide (ERG) Number	: 128
---------------------------------------	-------

**Other Information** : This product meets the limited quantities exemption as follows: DOT: Not regulated as dangerous goods when shipped in inner packagings equal to or less than 5L. Otherwise, the above descriptions apply.

### Transport by sea

Dot Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
-----------------------------	---

Limited Quantities (IMDG)	: 5 L
---------------------------	-------

# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special Provisions (IMDG)	: 223,363,955
Excepted Quantities (IMDG)	: E1
IBC Packing Instructions (IMDG)	: IBC03
Packing Instructions (IMDG)	: P001,LP01
Tank Instructions (IMDG)	: T4
Tank Special Provisions (IMDG)	: TP1,TP29
Stowage Category (IMDG)	: A
Properties and Observations (IMDG)	: Immiscible with water.
EMS-NO. (1)	: F-E
MFAG-NO	: 128
EMS-NO. (2)	: S-E
Marine Pollutant	: Yes

### Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75)	: 220 L
CAO Packing Instructions (IATA)	: 366
CAO Max Net Quantity (IATA)	: 220L
PCA Packing Instructions (IATA)	: 355
PCA Limited Quantities (IATA)	: Y344
PCA Limited Quantity Max Net Quantity (IATA)	: 10L
PCA Max Net Quantity (IATA)	: 60L
PCA Excepted Quantities (IATA)	: E1
CAO Max Net Quantity (IATA)	: 220L
CAO Packing Instructions (IATA)	: 366
Special Provision (IATA)	: A3
Erg Code (IATA)	: 3L
Instruction "cargo" (ICAO)	: 366
Instruction "cargo" - Limited Quantities (ICAO)	: 220L
Instruction "passenger" (ICAO)	: Y344
Instruction "passenger" - Limited Quantities (ICAO)	: 10L

## **SECTION 15: REGULATORY INFORMATION**

### US Federal Regulations

<b>ProStar Diesel Stabilizer</b>	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard Immediate (acute) health hazard
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>N,N'-Disalicylidene-1,2-propanediamine (94-91-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### US State Regulations

Neither this product nor its chemical components appear on any US state lists.

### Canadian Regulations

**Proprietary Polymer: HMIRA Registry Number 8129**

HMIRA Exemption Trade Secret exemption has been granted by the Commission.

HMIRA Filing/Grant Date 27-Mar-2012

<b>ProStar Diesel Stabilizer</b>	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects



# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



### Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

### N,N'-Disalicylidene-1,2-propanediamine (94-91-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

### Proprietary Polymer

WHMIS Classification	Class E - Corrosive Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision date</b>	: 03/15/2016
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H336	May cause drowsiness or dizziness
H371	May cause damage to organs
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

**NFPA Health Hazard** : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.



# ProStar Diesel Stabilizer

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

**NFPA Fire Hazard** : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

**NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

### Party Responsible for the Preparation of This Document

Star brite Inc.

Phone Number: (954)587-6280

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS